

# 1HM

中航电测 ZEMIC  
世界电测先锋



技术指标	
型号 MODEL	1HM
量程 CAPACITY	0.5kg、1kg   5kg、8kg、20kg
综合误差 COMPREHENSIVE ERROR	0.02
输出灵敏度 OUTPUT SENSITIVITY	1.0±0.15mV/V   1.5±0.1mV/V
非线性 NONLINEARITY	±0.02%F.S.
重复性 REPEATABILITY	±0.02%F.S.
滞后 HYSTERESIS	±0.02%F.S.
蠕变 CREEP	±0.02%F.S.5min
零点温度漂移 TEMP. EFFECT ON ZERO	±0.2%F.S./10℃
额定输出温度漂移 TEMP. EFFECT ON OUTPUT	±0.03%F.S./10℃
零点输出 ZERO OUTPUT	±0.1mV/V
输入电阻 INPUT RESISTANCE	1055±10 Ω
输出电阻 OUTPUT RESISTANCE	1000±10Ω
绝缘电阻 INSULATION RESISTANCE	≥2000MΩ (50V)
推荐激励电压 EXCITATION VOLTAGE	≤10 V
工作温度范围 OPERATION TEMP. RANGE	-10~+40℃
过载能力 OVERLOAD CAPACITY	150%F.S.
推荐用途 RECOMMENDED USE	厨房秤 kitchen scales 邮资秤 postage scales

